TITLE OF THE INVENTION

LIQUID CRYSTAL DISPLAY DEVICE AND DRIVING METHOD THEREOF

BACKGROUND OF THE INVENTION

5   FIELD OF THE INVENTION

This invention relates to a liquid crystal display device
and its driving method, more specifically, to a liquid crystal
display device and its driving method employing the horizontal
line inverting method.

10   DESCRIPTION OF THE RELATED ART

In general, the AC driving method is employed in liquid
crystal display devices. This is because the useful life becomes
short if the liquid crystal layer is driven with DC voltage.
Also well known as a driving method for reducing flicker during
15   AC driving is the horizontal line inverting method that inverts
polarity at every unit horizontal synchronization cycle (1H
cycle).

For example, as shown in FIG. 1, a liquid crystal display
device using this prior art driving method has a switching
20   circuit 107 that switches the outputs from a first standard
voltage generating circuit 106a that generates positive-polarity
standard voltage and a second standard voltage generating circuit
106b that generates negative-polarity standard voltage, in
synchronization with the synchronization signal provided by a
25   control circuit 101. The output of the switching circuit 107 is
connected in common to a plurality of horizontal drivers 103
connected to the signal lines of a liquid crystal panel 105.

The control circuit 101, responding to the input data for

the image displayed on the liquid crystal panel 105, makes the

horizontal drivers 103 apply the voltage provided from the first

standard voltage generating circuit 106a to the liquid crystal

panel 105, corresponding to the input gradation data for a unit

5   1H cycle. During the subsequent 1H cycle, it makes the

horizontal drivers 103 apply the voltage provided from the second

standard voltage generating circuit 106b to the liquid crystal

panel 105.

Further, the control circuit 101 makes a common voltage

10   generating circuit 104 apply a common voltage to the liquid

crystal panel 105. To the electrode of each pixel in the liquid

crystal panel 105, the horizontal driver 103 supplies a signal

voltage corresponding to the gradation data when a vertical

driver 102 has chosen a scanning line. Meanwhile, the common

15   voltage generating circuit 104 provides the common voltage for

the common electrode opposing this pixel electrode. Then an

image of gradation corresponding to the voltage gap between the

pixel electrode and the common electrode is displayed on the

liquid crystal panel 105. This common voltage is inverted at

20   every 1H cycle and supplied to the liquid crystal panel 105 in

order to enlarge the effective voltage applied to each pixel of

the liquid crystal panel 105. The AC driving of the liquid

crystal panel is performed by this line inversion at every 1H

cycle.

25   The gradation-γ correction voltage relation of a liquid

crystal display device is shown in FIG. 2A. The dotted line

represents the gradation-γ correction voltage relation that does

not take into account the applied voltage-transmittance property

of the liquid crystal layer, while the solid line represents the

gradation-γ correction voltage relation incorporating correction

that has taken into account the applied voltage-transmittance

property of the liquid crystal layer. Since the applied voltage-

5   transmittance property of the liquid crystal layer is not

represented with a straight line or is not linear, driving

voltage is applied to the liquid crystal panel based on the

gradation-γ correction voltage relation denoted with the solid

line in the diagram in order to realize gradation display

10   corresponding to the input data in actual liquid crystal display

devices.

If γ-correction voltage is applied to the liquid crystal

panel 105 of the prior art liquid crystal display device shown in

FIG. 1 based on the gradation-γ correction voltage relation

15   represented by the solid line, the applied voltage will be VF for

gradation X1, while VG for gradation X2 during the following 1H

cycle. Then the effective voltage applied to the liquid crystal

layer of the liquid crystal panel 105 will be $|VF-VC|$ and $|VG-VC|$,

respectively. Note that VC represents the common potential

20   supplied to the common electrode opposing the pixel electrode.

As a result, the effective voltage levels(F, G) differ from each

other between a 1H cycle and the subsequent 1H cycle, as shown in

FIG. 2B. This is the cause of flicker.

Besides, the circuit structure becomes complex in the

25   prior art liquid crystal display device shown in FIG. 1 because

the switching circuit 107 selects either standard voltage

generating circuit 106a or 106b each generating positive- or

negative-polarity standard voltage so as to supply standard

voltage to the horizontal drivers 103. Also because the power source voltage Vcc for the standard voltage generating circuits 106a, 106b is very high, the switching circuit 107 must withstand high voltage. Then the device cost will be high.

SUMMARY OF THE INVENTION

The object of the present invention is to provide a liquid crystal display device and driving method thereof that can reduce flicker with a relatively simple circuit structure by employing the line inversion driving technique.

A liquid crystal display device according to the present invention includes a liquid crystal panel having a plurality of scanning lines and a plurality of signal lines, a standard voltage generating circuit providing a plurality of standard voltages, a vertical driver that scans the scanning lines of said liquid crystal panel one after another, a horizontal driver that receives the plurality of standard voltages provided from said standard voltage generating circuit and supplies gradation voltage to the signal lines of said liquid crystal panel, and a control circuit that creates gradation data by inverting a polarity of input data for each horizontal synchronization cycle and controls the horizontal drivers so as to apply standard voltage corresponding to said gradation data to the liquid crystal panel. A gradation-γ correction voltage relation used by said control circuit for gradation display is symmetrical with respect to a point in a center between a top gradation step and a bottom gradation step.

In this liquid crystal display device, the gradation-γ

correction voltage relation is represented with a straight line and the horizontal driver applies γ correction voltage to the liquid crystal panel in response to the input gradation data to meet such a relation. The gradation-γ correction voltage

5   relation may not be represented with a straight line but, for example, a curved line or a polygonal line.

Such input data is, for example, digital data and the control circuit creates polarity-inverted gradation data by inverting each bit in the digital data.

10   Besides, if the standard voltage generating circuit has a ladder resistance, the gradation-γ correction voltage relation can be determined by setting the resistance values of the ladder resistance.

A driving method of a liquid crystal display device

15   according to the present invention includes the steps of supplying a plurality of standard voltages to horizontal drivers of a liquid crystal panel and scanning the liquid crystal panel with a vertical driver by inverting a polarity of input data for each line for displaying gradation. Said gradation-γ correction

20   voltage relation used in displaying gradation is symmetrical with respect to a point in a center between a top gradation step and a bottom gradation step.

In this case, the gradation-γ correction voltage relation is represented with a straight line, and the horizontal drivers

25   apply γ correction voltage to the liquid crystal panel in response to the input gradation data to meet the relation.

The gradation-γ correction voltage relation may not be represented with a straight line but, for example, a curved line

or a polygonal line.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a block diagram illustrating a prior art liquid crystal display device;

5   FIG. 2A is a graph showing the gradation-γ correction voltage relation used in the driving method for the prior art liquid crystal display device, and FIG. 2B is a waveform diagram showing the signals supplied to the liquid crystal panel based on the prior art driving method;

10   FIG. 3 is a block diagram illustrating the liquid crystal display device according to a first embodiment of the invention;

FIG. 4A is a graph showing the gradation-γ correction voltage relation used in the driving method for the liquid crystal display device according to the first embodiment of the

15   invention, and FIG. 4B is a waveform diagram showing the signals supplied to the liquid crystal panel based on this driving method; and

FIG. 5A is a graph showing the gradation-γ correction voltage relation used in the driving method for the liquid

20   crystal display device according to the second embodiment of the invention; and FIG. 5B is a waveform diagram showing the signals supplied to the liquid crystal panel based on this driving method.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

25   Now, embodiments of the present invention will be described in detail with reference to the accompanying drawings. FIG. 3 is a block diagram illustrating a liquid crystal display device according to a first embodiment of the present invention. The

liquid crystal display device according to the present embodiment

has a liquid crystal panel 5, a standard voltage generating

circuit 6, a vertical driver 2, a plurality of horizontal drivers

3, and a control circuit 1. The liquid crystal panel 5 is

5 equipped with a plurality of scanning lines and a plurality of

signal lines. The standard voltage generating circuit 6 provides

a plurality of standard voltages. The vertical driver 2 scans

the scanning lines of the liquid crystal panel 5 one after

another. The plurality of horizontal drivers 3 supply gradation

10 voltage to the signal lines of the liquid crystal panel 5

receiving the plurality of standard voltages from the standard

voltage generating circuit 6. The control circuit 1 creates

gradation data by inverting the polarity of the input data for

each unit horizontal synchronization cycle and then controls the

15 horizontal drivers 3 so as to provide the liquid crystal panel 5

with standard voltage corresponding to gradation data.

The standard voltage generating circuit 6 has a ladder

resistance connected in between the power source voltage Vcc and

the standard voltage and supplies 11-levels of standard voltage

20 V0-V10 to the plurality of horizontal drivers 3.

The control circuit 1 receives the digital input data of n-

bit and controls the horizontal driver 3 so that it supplies

voltage corresponding to this input data to the liquid crystal

panel 5 based on the above standard voltage during one horizontal

25 synchronization cycle (1H cycle). Further, the control circuit 1

creates polarity-inverted gradation data by inverting polarity of

each bit of the input data and, during the subsequent 1H cycle,

makes the horizontal drivers 3 provide the signal lines of the

liquid crystal panel 5 with voltage corresponding to the created

gradation data based on the above standard voltage. For example,

in the case of 64-step gradation, if the gradation X1 for a 1H

cycle is three (3), 60 is obtained as the gradation X2 for the

5   subsequent 1H cycle by inverting each bit of this 6-bit X1 (3).

If the gradation X2 for a 1H cycle is 60, the gradation X2 for

the subsequent 1H cycle becomes three (3) when each bit of this

6-bit data X2 (60) is inverted.

In addition, the control circuit 1 outputs signals of which

10 levels are inverted for each 1H horizontal synchronize cycle. A

common voltage output circuit 4 amplifies the level-inverted

signals and provides them as the common voltage for the common

electrode opposing the pixel electrode of the liquid crystal

panel 5. If this common voltage is level-inverted as well, the

15 effective voltage applied to the liquid crystal layer of the

liquid crystal panel 5 can be raised.

FIG. 4A is a graph demonstrating the gradation-γ

correction voltage relation used in driving the liquid crystal

display device according to the first embodiment of the

20 invention; and FIG. 4B is a waveform diagram showing the signals

supplied to the liquid crystal panel during the operation based

on the above driving method.

The solid line in FIG. 4A shows the positive-polarity

gradation-γ correction voltage relation, while the dot-dash line

25 shows the negative-polarity gradation-γ correction voltage

relation. In the present embodiment of the invention, the

gradation-γ correction voltage relation for gradation display is

symmetric with respect to a point in the center between the top

gradation step and the bottom gradation step and can be represented with a straight line. To meet such relation between gradation and voltage, in response to the input gradation data, the horizontal drivers 3 apply γ correction voltage to the signal

5 lines of the liquid crystal panel 5. In the case of a 64-step gradation, the top gradation step is 63, while the bottom one is zero.

The positive-polarity gradation-γ correction voltage relation is referred to when generating γ correction voltage to

10 be applied during a 1H cycle for the input gradation data, while the negative-polarity gradation-γ correction voltage relation is referred to when generating γ correction voltage to be applied during the subsequent 1H cycle. For example, the applied voltage for displaying gradation X1 will be VA with reference to the

15 positive-polarity gradation-γ correction voltage relation for a 1H cycle, while that for the subsequent 1H cycle will be VB with reference to the negative-polarity gradation-γ correction voltage relation. In this case, with VC being the central voltage of the level-inverted common voltage provided from the common voltage

20 output circuit 4, the effective voltages applied to the liquid crystal layer of the liquid crystal panel 5 will be $|VA-VC|$, $|VB-VC|$, respectively for the 1H cycle and the subsequent 1H cycle. Since the gradation-γ correction voltage relation is symmetrical with respect to a point, these absolute voltage differences(A, B)

25 become equal to each other(A=B), as illustrated in FIG. 4B.

Note that, as described above in the liquid crystal display device according to the present embodiment, polarity-inverted gradation data is created by inverting each bit of the input data

when the digital input signal of n-bit has been received. Then
the voltage corresponding to the gradation data is supplied to
the signal lines of the liquid crystal panel 5 based on the above
standard voltage for the subsequent 1H cycle. As a result, it

5 becomes possible to simplify the circuit structure, eliminating
the necessity for preparing a separate standard voltage
generating circuit for providing the negative-polarity gradation-
γ correction voltage relation.

As described above according to the liquid crystal display

10 device of the present invention, the structure of the standard
voltage generating circuit 6 that generates standard voltage can
be simplified because the gradation display is performed with
reference to the gradation-γ correction voltage relation which is
symmetrical with respect to a point in the center between the top

15 gradation step and the bottom gradation step and because the
control circuit 1 creates gradation data by inverting polarity of
the input data for each one horizontal synchronize cycle and then
applies the standard voltage corresponding to the gradation data
to the liquid crystal panel 5. Moreover, the useful life of the

20 liquid crystal panel 5 can be extended and its reliability can be
augmented because the absolute voltage difference between the
voltages applied to the pixel electrode and the common electrode
does not change between a 1H cycle and the subsequent 1H cycle.
Then flickers can be reduced because the absolute voltage

25 difference is kept constant.

Furthermore, in the driving method for the liquid crystal
display device according to the present embodiment, the
gradation-γ correction voltage relation is symmetrical with

respect to a point in the center between the top gradation step
and the bottom gradation step and the gradation-γ correction
voltage relation can be represented with a straight line. The
horizontal drivers 3 apply γ correction voltage to the signal
5   lines of the liquid crystal panel 5 in response to the input
gradation data so as to meet the gradation-γ correction voltage
relation. Then the absolute voltage differences applied to the
pixel electrode and the common electrode become equal (A=B)
during both a 1H cycle and the subsequent 1H cycle. Thereby the
10   useful life of the liquid crystal panel 5 can be extended and its
reliability can be augmented. Besides, flickers can be reduced
because the absolute voltage difference is kept constant.

Now a second embodiment of the present invention will be
described below. This second embodiment has a feature that the
15   gradation-γ correction voltage relation takes into account the
applied voltage-transmittance property of the liquid crystal
layer. Since its circuit configuration is almost the same as
that for the first embodiment shown in FIG. 3, its detail
description will not be referred to here.

20   FIG. 5A is a graph demonstrating the gradation-γ
correction voltage relations used in the driving method of the
liquid crystal display device according to the present invention;
and FIG. 5B is a waveform diagram showing the signals supplied to
the liquid crystal panel during the operation based on this
25   driving method. As shown in FIG. 5A in the present embodiment,
the gradation-γ correction voltage relation is symmetrical with
respect to a point in the center between the top gradation step
and the bottom gradation step, but not represented with a

straight line (in this embodiment, represented with a polygonal line). The horizontal drivers 3 apply γ correction voltage to the liquid crystal panel 5 in response to the input gradation data to meet the relation. This relation can be provided by

5   changing the resistance of each ladder resistance constituting the standard voltage generating circuit 6 of the liquid crystal display device shown in FIG. 3.

In the same manner as the first embodiment shown in FIG. 4A, the positive-polarity gradation-γ correction voltage relation

10   shown with the solid line in FIG. 5A is referred to when generating γ correction voltage to be applied during a 1H cycle for the input gradation data, while the negative-polarity gradation-γ correction voltage relation shown with the dot-dash line is referred to when generating γ correction voltage to be

15   applied during the subsequent 1H cycle. For example, the applied voltage for displaying gradation X3 will be VD with reference to the positive-polarity gradation-γ correction voltage relation for a 1H cycle, while that for the subsequent 1H cycle will be VE with reference to the negative-polarity gradation-γ correction

20   voltage relation. In this case, the effective voltages applied to the liquid crystal layer of the liquid crystal panel 5 will be $|VD-VC|$, $|VE-VC|$, respectively for the 1H cycle and the subsequent 1H cycle. Since the gradation-γ correction voltage relation is symmetrical with respect to a line, these voltage

25   differences in absolute values (D, E) become equal to each other (D=E), as illustrated in FIG. 5B.

This embodiment provides an advantage, in addition to the result attained in the first embodiment, that the line inversion

driving taking into account the applied voltage-transmittance property of the liquid crystal layer can be realized and then natural gradation can be realized on the liquid crystal display device. Besides, this advantage can be provided only by changing the individual values of the ladder resistances of the standard voltage generating circuit 6, with no need to add a separate circuit. Thus the increase in cost due to changes in circuit design is minimal.

The present invention has been described in details with respect to various embodiments, and it will now be apparent from the foregoing to those skilled in the art that changes and modifications may be made without departing from the invention in its broader aspects, and it is the invention, therefore, in the appended claims to cover all such changes and modifications as fall within the true spirit of the invention. For example, the gradation-γ correction voltage relation for use in displaying gradation is not limited those described in FIG. 4A and FIG. 5A but may be those represented with other curved lines and polygonal lines, instead of a straight line, as far as it is symmetrical with respect to a point in the center between the top gradation step and the bottom gradation step.

As described above, the liquid crystal display device according to this invention makes it possible to simplify and downsize the circuit configuration of the standard voltage generating circuit. Since the switch that switches the high voltage provided from the standard voltage generating circuit has been eliminated, the circuit configuration can be simplified and reduced in size. The power consumption can also be saved because

there is no switch that works at high voltage. Besides, in the

control circuit, the line inversion is performed at every 1H

cycle based on the gradation-γ correction voltage relation that

is symmetrical with respect to a line in the center between the

5   top gradation step and the bottom gradation step. As a result,

the effective voltage applied to the liquid crystal layer is kept

constant when polarity is inverted. Thus flickers are reduced.

     Furthermore, in the driving method for the liquid crystal

display device according to the present invention, the line

10   inversion is performed at every 1H cycle based on the gradation-

γ correction voltage relation which is symmetrical with respect

to a line in the center between the top gradation step and the

bottom gradation step. As a result, the effective voltage

applied to the liquid crystal layer is kept constant when

15   polarity is inverted. Thus flickers are reduced.